



Online Conductivity / Resistivity / TDS / Salinity Meter T6030

Function

Industrial online conductivity meter is a microprocessor-based water quality online monitoring control instrument, the salinometer measures and supervises the salinity (salt content) by conductivity measurement in fresh water. The measured value is displayed as ppm and by comparing the measured value to a user defined alarm set point value, relay outputs are available to indicate if salinity is above or below the alarm set point value.

Typical Use

This instrument is widely used in power plants, petrochemical industry, metallurgical electronics, mining industry, paper industry, medicine, food and beverage, water treatment, modern agricultural planting and other industries. It is suitable for softening water, raw water, steam condensate water, seawater distillation and deionized water, etc. It can continuously monitor and control the conductivity, resistivity, TDS, salinity and temperature of aqueous solutions.

Mains Supply

85~265VAC±10%,50±1Hz, power ≤3W;

9~36VDC, power consumption≤3W;

Measuring Range



Conductivity: 0~500ms/cm;

Resistivity: 0~18.25MΩ/cm;

TDS:0~250g/L;

Salinity: 0~700ppt;

Customizable measuring range, displayed in ppm unit.



Online Conductivity / Resistivity / TDS / Salinity Meter T6030

Features


1. Large display, standard 485 communication, with online and offline alarm, 144*144*118mm meter size, 138*138mm hole size, 4.3 inch large screen display.
2. The data curve recording function is installed, the machine replaces the manual meter reading, and the query range is arbitrarily specified, so that the data is no longer lost.
3. It can be matched with our high-quality stainless steel, PBT quadropole conductivity electrode, and the measurement range covers 0.00us/cm-500ms/cm to meet your measurement requirements for various working conditions.
4. Built-in conductivity/resistivity/salinity/total dissolved solids measurement functions, one machine with multiple functions, meeting the requirements of various measurement standards.
5. The design of the whole machine is waterproof and dustproof, and the back cover of the connection terminal is added to extend the service life in harsh environments.
6. Panel/wall/pipe installation, three options are available to meet various industrial site installation requirements.




Measurement mode



Calibration mode



Trend chart




Setting mode


Electrical connections

Electrical connection The connection between the instrument and the sensor: the power supply, output signal, relay alarm contact and the connection between the sensor and the instrument are all inside the instrument. The length of the lead wire for the fixed electrode is usually 5-10 meters, and the corresponding label or color on the sensor Insert the wire into the corresponding terminal inside the instrument and tighten it.

Instrument installation method




Schematic of completion of installation




- a. Embedded in an open hole
- B. Fix the instrument

Embedded installation



Instrument installation: Wall mounted installation



Schematic of completion of installation



- A. Install a mounting bracket for the instrument
 - B. Wall screw fixation
- Top view of mounting bracket
Pay attention to installation direction



Wall mount

Technical specifications

Conductivity	0~500mS/cm
Resolution	0.1 us/cm;0.01ms/cm
Intrinsic error	±0.5%F.S
Resistivity	0~18.25MΩ/cm
Resolution	0.01KΩ/cm;0.01MΩ/cm
TDS	0~250g/L
Resolution	0.01mg/L;0.01g/L
Salinity	0~700ppt
Resolution	0.01ppm;0.01ppt
Temperature	-10~150°C
Resolution	±0.3°C
Temperature compensation	Automatic or manual
Current output	2 Rd 4~20mA
Communication output	RS 485 Modbus RTU
Other function	Data recording, curve display, data uploading
Relay control contact	3 Groups: 5A 250VAC,5A 30VDC
Optional power supply	85~265VAC,9~36VDC, Power: ≤3W
The work environment	In addition to the earth's magnetic field around no strong magnetic field interference
The environmental temperature	-10~60°C
Relative humidity	No more than 90%
Protection grade	IP65
The instrument weight	0.8kg
Instrument dimensions	144*144*118mm
Mounting hole dimensions	138*138mm
Installation	Embedded, wall - mounted, pipeline